



your local global brand

Gulf Racing 10W-60

Fully Synthetic Passenger Car Motor Oil

Product Description:

Gulf Racing SAE 10W-60 is a fully synthetic motor oil of exceptional quality for extreme performance in gasoline- and diesel engines under very heavy load and temperature conditions. **Gulf Racing SAE 10W-60** has been especially developed to withstand high pressures and temperatures during racing conditions.

Formulated from a blend of synthetic base fluids gives **Gulf Racing SAE 10W-60** outstanding thermal stability, improved viscosity-temperature characteristics, exceptional low temperature fluidity, reduces friction and increases power.

Gulf Racing SAE 10W-60 reduces oil and fuel consumption, reduces friction and wear, keeps the internal parts of the engine cleaner, gives longer life-span of the engine and the oil and has optimum viscosity characteristics.

Gulf Racing SAE 10W-60 is applicable for gasoline - and diesel engines of passenger cars and light trucks that have to perform in extreme conditions.

Specifications:

Meets: ACEA A3/B4, API SL/CF

Properties:	Test Methods:	Typical Values:
SAE Viscosity Grade	SAE J300	10W-60
Density @ 15°C	ASTM D4052	844 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	173 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	24 mm ² /s (cSt)
Viscosity Cold-Cranking Simulator @ -20°C	ASTM D5293	<7000 mPa.s (cP)
Viscosity Index	ASTM D2270	170
Flash Point (COC)	ASTM D92	>200°C
Pour Point	ASTM D97	-33°C
Total Base Number	ASTM D2896	11.4 mgKOH/g
Sulphated Ash	ASTM D874	1.3 wt %

Product Code: 1125

Date Issued: 28/11/2011

Date Superseded: 21/09/2011

Revision nr: 03