



your local global brand

Gulf Formula G 5W-30

Fully Synthetic Passenger Car Motor Oil

Product Description:

Gulf Formula G 5W-30 is a supreme performance passenger car motor oil formulated from finest quality synthetic base stocks and state-of-the-art additive technology and has been specially developed for all modern turbocharged, high output gasoline and diesel engines of passenger cars, SUVs, light vans and trucks. **Gulf Formula G 5W-30** has been designed to deliver long service life and minimizes deposits in engine and turbocharger to ensure rated engine power and torque.

Gulf Formula G 5W-30 has outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended oil & engine life and improved fuel economy and extended drain intervals reduces the cost of ownership. Excellent low temperature fluidity aids quick cold start and provides wear protection at start-up and outstanding Stay-in-Grade performance ensures reliable lubrication even at higher load and operating temperatures. Superior antiwear technology provides excellent wear protection under all conditions and active cleaning agents ensure maximum engine cleanliness.

Gulf Formula G 5W-30 is recommended for all modern vehicles including high performance, turbo-charged, multi valve, direct injection gasoline and diesel engines of passenger cars and exceeds the requirements of most modern European, North American and Japanese passenger cars including gasoline powered racing cars.

Specifications:

Meets: ACEA A3/B4, VW 502.00/505.00

Approved by: API SL/CF, MB-Approval 229.3, BMW Longlife-98

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
SAE Viscosity Grade	SAE J300	5W-30
Density @ 15°C	ASTM D4052	852 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	63.3 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	11.2 mm ² /s (cSt)
Viscosity Cold-Cranking Simulator @ -30°C	ASTM D5293	6200 mPa.s (cP)
Viscosity Index	ASTM D2270	170
Flash Point (COC)	ASTM D92	234°C
Pour Point	ASTM D97	-42°C
Total Base Number	ASTM D2896	10.1 mgKOH/g
Sulphated Ash	ASTM D874	1.26 wt %

Product Code: 1217

Date Issued: 28/11/2011

Date Superseded: 25/10/2011

Revision nr: 03