



your local global brand

Gulf MAX Plus 15W-40

Passenger Car Motor Oil

Product Description:

Gulf MAX Plus 15W-40 is a generation passenger car motor oils developed for the latest high performance passenger cars & light duty vehicles powered by gasoline and diesel engines. The advanced additive technology incorporated in **Gulf MAX Plus 15W-40** enables it to exceed the performance requirements of leading passenger car manufacturers' and global industry standards.

Gulf MAX Plus 15W-40 has superior dispersants that provide excellent control over soot induced oil thickening and better thermo-oxidative stability minimise deposits & sludge build-up facilitating extended oil life. Active cleaning agents provide engine cleanliness and good antiwear technology minimises engine wear and thereby reduces maintenance costs and special rust inhibitors retard the formation of rust & corrosion in critical engine parts.

Gulf MAX Plus 15W-40 is recommended for high performance, multi valve, turbocharged & supercharged gasoline and diesel powered passenger cars and light duty vehicles requiring ACEA A3/B3 & API SL/CF quality oils.

Gulf MAX Plus 15W-40 is recommended for all vehicles requiring MB-Approval 229.1 quality oils.

Specifications:

Meets: ACEA A3/B3, VW 505.00

Approved by: API SL/CF, MB-Approval 229.1

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
SAE Viscosity Grade	SAE J300	15W-40
Density @ 15°C	ASTM D4052	891 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	106 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	14.2 mm ² /s (cSt)
Viscosity Cold-Cranking Simulator @ -20°C	ASTM D5293	6340 mPa.s (cP)
Viscosity Index	ASTM D2270	136
Flash Point (COC)	ASTM D92	224°C
Pour Point	ASTM D97	-33°C
Total Base Number	ASTM D2896	8.75 mgKOH/g
Sulphated Ash	ASTM D874	1.2 wt %

Product Code: 1320

Date Issued: 28/11/2011

Date Superseded: 25/10/2011

Revision nr: 03