



your local global brand

Gulf Multi G 20W-50

Passenger Car Motor Oil

Product Description:

Gulf Multi G 20W-50 is a passenger car motor oil designed for older gasoline powered passenger cars and naturally aspirated diesel engines of light duty vehicles. **Gulf Multi G 20W-50** is blended using good quality base oils and performance additives to ensure better engine protection.

Gulf Multi G 20W-50 has good thermo-oxidative stability that minimises deposits & sludge build-up, effective rust inhibitors retard formation of rust in critical engine parts, antiwear technology minimises engine wear & reduces maintenance costs and good stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures.

Gulf Multi G 20W-50 is recommended for use in passenger cars, light trucks and vans with naturally aspirated gasoline engines or light-duty diesel engines, where API SF/CD quality oil is required and is suitable for year-round use under wide temperature conditions and ensures trouble free operation.

Specifications:

Meets: API SF/CD

Properties:	Test Methods:	Typical Values:
SAE Viscosity Grade	SAE J300	20W-50
Density @ 15°C	ASTM D4052	891 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	170 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	18.6 mm ² /s (cSt)
Viscosity Cold-Cranking Simulator @ -15°C	ASTM D5293	9100 mPa.s (cP)
Viscosity Index	ASTM D2270	123
Flash Point (COC)	ASTM D92	238°C
Pour Point	ASTM D97	-24°C
Total Base Number	ASTM D2896	5.4 mgKOH/g
Sulphated Ash	ASTM D874	067 wt %

Product Code: 1335

Date Issued: 28/11/2011

Date Superseded: 25/10/2011

Revision nr: 03