



your local global brand

# Gulf Single G 50

*Passenger Car Motor Oil*

**Product Description:**

**Gulf Single G 50** is a passenger car motor oil designed for older gasoline powered passenger cars and naturally aspirated diesel engines of light duty vehicles requiring mono-grade engine oils.

**Gulf Single G 50** is blended using good quality base oils and performance additives to ensure better engine protection. **Gulf Single G 50** is developed to exceed the performance requirements of API (American Petroleum Institute) SF/CD.

**Gulf Single G 50** has good thermo-oxidative stability minimizes deposits & sludge build-up, effective rust inhibitors retard formation of rust in critical engine parts. Better antiwear technology minimizes engine wear & reduces maintenance costs and good stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures.

**Gulf Single G 50** is recommended for use in passenger cars, light trucks and vans with naturally aspirated gasoline engines or light-duty diesel engines, where API SF/CD quality oil is required.

**Specifications:**

**Meets:** API SF/CD

| <b><u>Properties:</u></b>   | <b><u>Test Methods:</u></b> | <b><u>Typical Values:</u></b> |
|-----------------------------|-----------------------------|-------------------------------|
| SAE Viscosity Grade         | SAE J300                    | 50                            |
| Density @ 15°C              | ASTM D4052                  | 898 kg/m <sup>3</sup>         |
| Kinematic Viscosity @ 40°C  | ASTM D445                   | 204 mm <sup>2</sup> /s (cSt)  |
| Kinematic Viscosity @ 100°C | ASTM D445                   | 18.2 mm <sup>2</sup> /s (cSt) |
| Viscosity Index             | ASTM D2270                  | >95                           |
| Flash Point (COC)           | ASTM D92                    | 248°C                         |
| Pour Point                  | ASTM D97                    | -18°C                         |
| Total Base Number           | ASTM D2896                  | 5.4 mgKOH/g                   |
| Sulphated Ash               | ASTM D874                   | 0.67 wt %                     |

Product Code: 1395

Date Issued: 28/11/2011

Date Superseded: 25/10/2011

Revision nr: 03