



Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 1/9/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Diesel 10ppm B7
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Fuel

Title	Life cycle stage	Use descriptors
Diesel 10ppm B7	Industrial, Professional	PC13, PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC9, PROC14, PROC15, PROC16, ERC2, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC7, ERC9a, ERC9b

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FinCo Supply & Trading
Mijlweg 61
3316 BE Dordrecht - The Netherlands
T +31 88 021 51 00
info@fincofuel.com - www.fincofuel.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Carcinogenicity, Category 2 H351
Specific target organ toxicity — Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

GHS09

Signal word (CLP)

: Danger

Hazardous ingredients

: Fuels, diesel

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H332 - Harmful if inhaled.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs (liver, bone marrow, thymus) through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe vapours.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection, face protection, protective clothing.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Extra phrases

: For professional users only.

2.3. Other hazards

Other hazards not contributing to the classification

: Vapour could form explosive mixture with air. The vapours are denser than air and may travel along the ground. Distance ignition possible. On heating there is a risk of a build-up of pressure in hermetically sealed containers or tanks. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment). Used in closed systems.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fuels, diesel	(CAS-No.) 68334-30-5 (EC-No.) 269-822-7 (EC Index-No.) 649-224-00-6 (REACH-no) 01-2119484664-27	90 - 95	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Fatty acids, C14-18 and C16-18-unsatd., Me esters	(CAS-No.) 67762-26-9 (EC-No.) 267-007-0 (REACH-no) 01-2119471662-36	5 - 10	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Inhalation of the product into the lungs may cause very serious pneumonia. In case of loss of conscience place the victim in the recovery position. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Keep under medical supervision for at least 48 hours. IF INHALED: In case of unconsciousness place in unconscious position and seek medical advice. Give oxygen or artificial respiration as needed. IF SWALLOWED: Rinse mouth, do not induce vomiting. (If vomiting occurs, keep head low so that stomach content doesn't get into lungs.)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Alcohol-resistant foam. Dry powder. Making extinguishing agents environment-friendly.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. Vapours are heavier than air and may spread along floors, but not explosive under storage and transfer conditions. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Explosion hazard	: Saturated vapor pressure is below the LEL in atmospheric storage and handling conditions (see 9.1). No explosion hazard.
Reactivity in case of fire	: Combustion produces irritating gases.
Hazardous decomposition products in case of fire	: Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapours sulphur oxides.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Warning! Product may cause floors to be slippery. Wear personal protective equipment. Ensure adequate air ventilation. Avoid breathing dust, mist or spray. Do not get in eyes, on skin, or on clothing. Stop leak if safe to do so. No flames, no sparks. Eliminate all sources of ignition. Use spark-/explosionproof appliances and lighting system. Do not smoke. Keep public away from danger area.
------------------	--

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

Emergency procedures : Block the system, isolate it and make it voltage-free. Attention exposure to liquid and vapor (max. 0.1% vol / vol, 1000 ppmv).

6.1.2. For emergency responders

Emergency procedures : Block the system, isolate it and make it voltage-free. Attention exposure to liquid and vapor (max. 0.1% vol / vol, 1000 ppmv). Let switch off electrical equipment or other possible sources of ignition.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. Take up liquid spill into absorbent material. If possible, allow spill to evaporate under surveillance. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Store away from other materials.
Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Combustible liquid. Vapours are heavier than air and spread above ground. Vapours are heavier than air and may spread along floors, but not explosive under storage and transfer conditions.
Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Block the system, isolate it and make it voltage-free. Attention exposure to liquid and vapor (max. 0.1% vol / vol, 1000 ppmv).
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Vapours are heavier than air and spread above ground.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Containers which are opened should be properly resealed and kept upright to prevent leakage.
Information on mixed storage : Keep away from: Oxidizer.
Packaging materials : Suitable material: Stainless steel. Carbon steel. Plastics (HDPE).

7.3. Specific end use(s)

No supplementary information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fuels, diesel (68334-30-5)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	0.05 mg/m ³ (The limit value shall apply from 21 February 2023. For underground mining and tunnel construction the limit value shall apply from 21 February 2026)
--------------------------------	--

Fuels, diesel (68334-30-5)

DNEL/DMEL (Workers)

Acute - systemic effects, dermal	11.11 mg/kg bodyweight/day
----------------------------------	----------------------------

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Fuels, diesel (68334-30-5)	
Acute - systemic effects, inhalation	102.7 ng/m ³
Long-term - systemic effects, dermal	2.9 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	68.3 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	2600 mg/m ³
Long-term - systemic effects, oral	1.3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	20 mg/m ³
Long-term - systemic effects, dermal	1.3 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	21 µg/l
Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	10 mg/kg bw/day
Long-term - systemic effects, inhalation	6.69 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	5 mg/kg bw/day
Long-term - systemic effects, inhalation	23 mg/m ³
Long-term - systemic effects, dermal	5 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	2.504 mg/l
PNEC aqua (marine water)	0.25 mg/l
PNEC aqua (intermittent, freshwater)	25.04 mg/l
PNEC (STP)	
PNEC sewage treatment plant	520 mg/l

8.2. Exposure controls

Appropriate engineering controls:

Provide sufficient air exchange and/or exhaust. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): e.g. nitrile rubber (>=0.4 mm), butyl rubber (>=0.7 mm) and others. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Wear safety glasses with side shields or face shield (EN 166)

Skin and body protection:

Wear suitable protective clothing (EN 14605). Standard (EN 1149-5) Protective clothing: Flame retardant antistatic properties. Safety boots or safety shoes.

Respiratory protection:

Provide sufficient air exchange and/or exhaust. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A2 according to standard EN 14387) is used. Consult respiratory device supplier's product information for the selection of the appropriate device.

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Environmental exposure controls:

Avoid release to the environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. If on skin, take off contaminated clothing. Keep away from food, drink and animal feedingstuffs. Avoid contact with skin and eyes. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: clear.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -40 - 6 °C @ 101.325 kPa
Freezing point	: No data available
Boiling point	: 141 - 462 °C @ 101.3 kPa
Flash point	: > 55 °C @ 101.325 kPa
Auto-ignition temperature	: 225 °C @ 101.325 kPa
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 4 hPa @ 40 °C < 1 mbar (1 hPa) @ 15 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.82 - 0.845 g/cm ³ @ 15 °C
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 4.15 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.6 - 6.5 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour. The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable in use and storage conditions as recommended in item 7.

10.3. Possibility of hazardous reactions

Flammable liquid and vapour. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Keep away from: Oxidizing agents and strong acids. Bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Carbon monoxide. Carbon dioxide. Hydrogen sulfide.

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Diesel 10ppm B7

ATE dust/mist	1.613 mg/l/4h
---------------	---------------

Fuels, diesel (68334-30-5)

LD50 oral rat	21.1 ml/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	3.6 - 5.4 mg/l/4h

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (EPA OPPTS 870.1200: Acute Dermal Toxicity, Rabbit, Read-across, Dermal)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (liver, bone marrow, thymus) through prolonged or repeated exposure.

Fuels, diesel (68334-30-5)

NOAEL (dermal, rat/rabbit, 90 days)	≈ 2000 mg/kg bodyweight Animal: rabbit
-------------------------------------	--

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	--

Aspiration hazard	: May be fatal if swallowed and enters airways.
-------------------	---

Diesel 10ppm B7

Viscosity, kinematic	4.15 mm ² /s @ 40 °C
----------------------	---------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

EC50 Daphnia	2504 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, Nominal concentration)
--------------	--

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 72h algae (1)	> 0.131 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 (algae)	73729 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, Nominal concentration)

12.2. Persistence and degradability

Diesel 10ppm B7

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Fuels, diesel (68334-30-5)

Persistence and degradability	Contains readily biodegradable component(s).
-------------------------------	--

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

Diesel 10ppm B7

Bioaccumulative potential	Moderately bioaccumulative.
---------------------------	-----------------------------

Fuels, diesel (68334-30-5)

Log Pow	3 - 6 (Literature)
Bioaccumulative potential	Contains bioaccumulative component(s).

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

BCF other aquatic organisms 1	3 (Equivalent or similar to OECD 305, 20 day(s), Mytilus edulis, Salt water, Read-across, Fresh weight)
Log Pow	> 6.2 (Read-across, EU Method A.8: Partition Coefficient, 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Fuels, diesel (68334-30-5)

Ecology - soil	Contains component(s) with potential for mobility in the soil.
----------------	--

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)

Log Koc	> 5.63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Read-across)
Ecology - soil	Adsorbs into the soil.

12.5. Results of PBT and vPvB assessment

Component

Fatty acids, C14-18 and C16-18-unsatd., Me esters (67762-26-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Fuels, diesel (68334-30-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapours may accumulate in the container. Do not empty into drains.
Ecology - waste materials : Avoid release to the environment.
European List of Waste (LoW) code : 13 07 01* - fuel oil and diesel
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADN / ADR / IATA / IMDG / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1202	UN 1202	UN 1202	UN 1202	UN 1202
14.2. UN proper shipping name				
DIESEL FUEL	DIESEL FUEL	Diesel fuel	DIESEL FUEL	DIESEL FUEL
Transport document description				
UN 1202 DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1202 Diesel fuel, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user


Special transport precautions : See Heading 7

Classification code (ADR) : F1
Special provisions (ADR) : 640K, 664
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: 3Y
Special provisions (IMDG)	: 363
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Immiscible with water.
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L
Classification code (ADN)	: F1
Special provisions (ADN)	: 640K
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0
Additional requirements/Remarks (ADN)	: Table: C. Danger: 3+(N2+F)
Classification code (RID)	: F1
Special provisions (RID)	: 640K
Limited quantities (RID)	: 5L

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3(a)	Diesel 10ppm B7 ; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Diesel 10ppm B7 ; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Diesel 10ppm B7 ; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Diesel 10ppm B7 ; Fuels, diesel	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
EC50	Median effective concentration
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Other information : **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Full text of use descriptors

ERC2	Formulation into mixture
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC5	Use at industrial site leading to inclusion into/onto article
ERC6a	Use of intermediate
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)
ERC6c	Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
ERC7	Use of functional fluid at industrial site

Diesel 10ppm B7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ERC9a	Widespread use of functional fluid (indoor)
ERC9b	Widespread use of functional fluid (outdoor)
PC13	Fuels
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC14	Tabletting, compression, extrusion, pelettisation, granulation
PROC15	Use as laboratory reagent
PROC16	Use of fuels
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Carc. 2	H351	Calculation method
STOT RE 2	H373	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II) - Finco

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.